

**This Page Is Inserted by IFW Operations  
and is not a part of the Official Record**

## **BEST AVAILABLE IMAGES**

**Defective images within this document are accurate representations of the original documents submitted by the applicant.**

**Defects in the images may include (but are not limited to):**

- **BLACK BORDERS**
- **TEXT CUT OFF AT TOP, BOTTOM OR SIDES**
- **FADED TEXT**
- **ILLEGIBLE TEXT**
- **SKEWED/SLANTED IMAGES**
- **COLORED PHOTOS**
- **BLACK OR VERY BLACK AND WHITE DARK PHOTOS**
- **GRAY SCALE DOCUMENTS**

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problems Mailbox.**

**THIS PAGE BLANK (USPTO)**

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau




SIN 10/049,072  
6-48  
3629  
384

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification n<sup>4</sup> : <b>F16D 7/00</b></p>	<p><b>A1</b></p>	<p>(11) International Publication Number: <b>WO 90/00231</b> 5,069,320 (43) International Publication Date: <b>11 January 1990 (11.01.90)</b></p>
<p>(21) International Application Number: <b>PCT/SE89/00371</b> (22) International Filing Date: <b>29 June 1989 (29.06.89)</b> (30) Priority data: 8802498-9      4 July 1988 (04.07.88)      <b>SE</b> (71) Applicant (for all designated States except US): <b>METALFORM SAFESSET AB [SE/SE]; Kabelvägen 13, S-824 00 Hudiksvall (SE).</b> (72) Inventor; and (75) Inventor/Applicant (for US only) : <b>FALK, Curt 24 [SE/SE]; Kråkövägen 24, S-824 00 Hudiksvall (SE).</b> (74) Agents: <b>ASTBERG, Åke et al.; P.O. Box 15085, S-104 65 Stockholm (SE).</b></p>		<p>(81) Designated States: <b>AT (European patent), BE (European patent), CH (European patent), DE (European patent), FR (European patent), GB (European patent), IT (European patent), JP, LU (European patent), NL (European patent), SE (European patent), US.</b>  <b>Published</b> <i>With international search report. In English translation (filed in Swedish).</i></p>

(54) Title: A TORQUE-LIMITING COUPLING DEVICE



(57) Abstract

The invention relates to a torque-limiting clutch arrangement which comprises a cylindrical part (3) forming part of one clutch element and having shrink-fitted thereon a cylindrical sleeve (5) which forms part of the other clutch element. The clutch arrangement also includes pump means which when one clutch element (3) rotates relative to the other clutch element (5), when the torque on the clutch exceeds a given value, functions to pump oil into the domain of engagement between the cylindrical part (3) and the sleeve (5), so as to form a hydrostatic layer therebetween, this layer essentially negating the friction between the engagement surfaces while the relative movement continues.

***FOR THE PURPOSES OF INFORMATION ONLY***

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FI	Finland	ML	Mali
AU	Australia	FR	France	MR	Mauritania
BB	Barbados	GA	Gabon	MW	Malawi
BE	Belgium	GB	United Kingdom	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IT	Italy	RO	Romania
BJ	Benin	JP	Japan	SD	Sudan
BR	Brazil	KP	Democratic People's Republic of Korea	SE	Sweden
CF	Central African Republic	KR	Republic of Korea	SN	Senegal
CG	Congo	LI	Liechtenstein	SU	Soviet Union
CH	Switzerland	LK	Sri Lanka	TD	Chad
CM	Cameroon	LJ	Luxembourg	TG	Togo
DE	Germany, Federal Republic of	MC	Monaco	US	United States of America
DK	Denmark	MG	Madagascar		
ES	Spain				

## A TORQUE-LIMITING COUPLING DEVICE

The present invention relates to a torque-limiting clutch arrangement which comprises two mutually coaxial clutch elements which are non-rotatably connected to a driving shaft and a driven shaft respectively and which engage one another through the intermediary of two mutually opposing, pressurized surfaces, therewith forming a friction joint which is dimensioned to slip when the torque on the clutch exceeds a predetermined value; and a device which is operative to detect slip occurrences in the friction joint and to disengage or separate the clutch elements when slip occurs.

Torque-limiting clutches or couplings of this kind are known to the art in many different forms. The clutch normally has the form of a conventional disc-clutch comprising a pressure plate which is applied by means of a powerful spring force. When slip occurs, a device comes into function and relieves the pressure on the pressure plate, so as to disengage the clutch. In the case of one simple design, described and illustrated in DE 22 15 053, the spring pressure is generated by compressed-air springs which are pressurized via a compressed-air conduit. This conduit communicates with an outwardly projecting nipple mounted on one clutch element. The nipple is closed at one end and when relative rotation occurs between the two clutch elements, the nipple is punctured by a moveable member provided on the other of said clutch-elements.

Such a clutch arrangement is both complicated and space-demanding, particularly when intended for high torques. Another drawback with a clutch of this kind is that once

the clutch is overloaded, so that the clutch is disengaged and the driven shaft has stopped, the clutch cannot be reengaged until the nipple has been replaced and the compressed-air springs repressurized.

5

The object of the present invention is to provide a clutch of the kind described in the introduction which is of simple and reliable construction and which will remain reliable, even after several years in use; which is particularly adapted for high torques; and which when disengaged under overload conditions is ready for re-use immediately, without needing to replace any of the clutch components or to take any other form of remedial action with respect to the clutch.

15

This object is achieved with a clutch constructed in accordance with the invention and having the characteristic features set forth in the following claims. Considered as a clutch arrangement, the inventive arrangement has the simplest and most-compact construction possible, namely a cylindrical sleeve which is clamped rigidly, preferably shrink-fitted, onto a cylindrical part. Moveable parts, i.e. pump means driven by mutual rotation of the cylindrical parts, do not begin to function until slip occurs between the cylindrical parts as a result of an overload. Pressure fluid is delivered to a pressure conduit at the requisite pressure, such as to force the fluid through openings provided in at least one of said friction surfaces and produce a hydrostatic layer which separates the two cylindrical parts so that the friction generated therebetween will be at a minimum. Immediately upon cessation of the mutual rotation of said parts, the pump means will cease to operate and the hydrostatic layer is dispersed so as to reestablish

30

frictional contact between the clutch elements. A closed pressure-fluid circuit is obtained, by providing drainage channels in at least one of said friction surfaces, said circuit enabling the clutch to be held disengaged  
5 over a long period of time, if necessary.

The invention will now be described in more detail with reference to the accompanying drawing, in which Figure 1 is a longitudinal sectional view of a preferred embodiment of an inventive clutch arrangement, and Figure 2  
10 illustrates schematically alternative positioning of the pump units of said arrangement.

Shown in the drawing is a drive shaft 1 which is keyed  
15 by a key 2 to a first clutch or coupling element comprising a first cylindrical sleeve 3 which is press-fitted on one end of the drive shaft and the free-end of which has a first hub 4 firmly mounted thereon. A second or outer sleeve 5 having mounted thereon a second hub 6  
20 and belonging to a second clutch element is shrink-fitted on the outer cylindrical surface of the first sleeve 3. The second hub 6 has provided therein a central hole in which there is firmly mounted a journal pin 7, the end of which facing the drive shaft 1 is connected to said shaft through the intermediary of a  
25 roller bearing 8. The second hub 6 is configured as a flange-connection for a driven shaft, e.g. a cardan shaft in an electrically driven unit intended for a track-driven vehicle or the like.

30

The first hub 4 incorporates six radially extending piston pumps 10, which are uniformly placed around the hub. Each pump includes a radial bore 11 which accommodates a piston 12, said piston being driven by a

strong pressure-spring 13, located between the outer end of the piston and a closure 14. The spring 13 presses the inwardly located end of the piston 12 against an outer-ring 15 of a needle-bearing, the inner-ring 16 of which is mounted on an excentric 17 formed on the journal pin 7. The piston 12 is provided in a conventional manner with a suction opening 18, an axial through-flow channel 19, a suction valve 20 mounted in said channel, and a pressure opening 21.

The suction opening 18 communicates with a suction passage 22 which extends axially through the first hub 4, whereas the pressure opening 21 communicates with a pressure passage 23 which also extends through the first hub 4. Located opposite the orifice of the pressure passage 23 is an axial outlet channel 24. The channel 24 incorporates a pressure valve 25 which coacts with the pump 10, in a known manner.

A radial channel 26 connects the outlet channel 24 with a peripheral groove 27 in the outer cylindrical wall 28 of the first sleeve 3. Each of the other five pumps 10 is provided with a peripheral groove, in a corresponding manner. As illustrated in the upper part of Figure 1, a further outlet channel 24' is connected to a further peripheral groove 27', via a further radial channel 26'. The peripheral grooves 27, 27' are uniformly spaced in the axial direction. Arranged externally of the groove 27" distal from the first hub 4 is a peripheral drainage groove 29 which communicates, via a drainage passage 30, with an annular pressure-fluid storage container 31 located between the clutch elements. The container 31 communicates solely with the suction passages 22 of respective piston pumps 10 and with the drainage passage



30. Two closing devices 32 and 33, not shown in detail, are provided for the purpose of filling the system with pressure fluid, preferably oil, and of ventilating the closed fluid system.

5

In normal operation, the inventive clutch arrangement functions as a friction clutch having two clutch sleeves which are joined by a shrink-joint, said joint being adapted so that clutch-slip will only occur when the torque applied to the clutch reaches a predetermined, maximum permitted value.

When this value is reached, the first sleeve 3 and the first hub 4 will rotate relative to the second sleeve 5 and the second hub 6 carrying the journal pin 7 and the excentric 17. The pistons 12 will then be forced outwards in succession and with great force, by the excentric needle-bearing 15, 16, and then returned by the springs 13. When the pressure-fluid system is filled with oil, oil will consequently be pressed into the peripheral grooves 27, thereby separating the two sleeves 3, 5 sufficiently to enable the oil to leave the grooves 27 and enter the drainage passage 29, from where the oil flows through the drainage passage 30 and back to the container 31. There is thus formed between the first and second sleeves 3 and 5 a hydrostatic layer which will permit the sleeves to rotate mutually with only very little friction therebetween.

Slipping between the sleeves 3 and 5 will stop immediately the torque acting on the clutch has fallen to a sufficiently low level. The pumps 10 will then cease to work and the oil in the grooves 27 will lose its pressure. Consequently, the oil is forced away from the

interspace between the grooves 27, and the two sleeves 3 and 5 are then restored to frictional engagement as a result of the shrink joint.

5 The illustrated and described clutch arrangement is intended primarily for use with rapid-speed clutches or couplings which operate with one pump-stroke per revolution and pump. In the case of slower clutches it may be more expedient to use a cam-curve which enables  
10 more pump-strokes to be effected per revolution and pump. In this case, the pump units can then be disposed axially, as shown schematically in Figure 2. This illustration shows separate piston-pumps 40 mounted externally on the outer or second sleeve 5 of the clutch arrangement, and a cam-curve 41 mounted rigidly on the  
15 shaft 1. Piston rods 42 provided with roller-type cam-followers 42 transmit pumping movement from the cam-curve 41 to the pistons of the pumps (not shown) when relative movement occurs between the outer sleeve 5 and  
20 the shaft 1. With the exception of the pumps 10 and the excentric 17, the clutch shown in Figure 2 is the same as that shown in Figure 1, although in the case of the Figure 2 embodiment it may be expedient to form the peripheral grooves 27 with associated passages in the  
25 outer sleeve 5, since the pumps 40 are mounted on said sleeve.

It will be understood that the invention is not restricted to the illustrated and described embodiments and  
30 that various modifications can be made within the scope of the invention defined in the following claims, for instance, the piston-pumps 40 of the Figure 2 embodiment can be mounted in axial bores in the wall of the outer sleeve 5, in a manner corresponding to the pumps 10 in

the radial bores 11 provided in the first hub 4. The number of pumps can, of course, vary in dependence on the pressure-fluid requirement.

## CLAIMS

1. A torque-limiting clutch arrangement comprising two mutually coaxial clutch elements which are non-rotably  
5 connected to a driving shaft and a driven shaft respectively and which engage one another through the intermediary of two mutually opposing, pressurized surfaces forming a friction-joint which is dimensioned to slip  
10 when the torque on the clutch exceeds a predetermined value; and a device for detecting slip occurrences in the friction-joint and to disengage the clutch when slip occurs, characterized in that the friction-joint  
comprises a cylindrical part (3) which is rigidly connected to one clutch element and which has press-fitted  
15 thereon a cylindrical sleeve (5) which is connected rigidly to the other clutch element, and further comprises a high-pressure pump means (10) which is driven  
by the detecting device (17) such as to supply pressure-fluid to an outlet passage (24) when slip occurs in the  
20 friction-joint, and a plurality of openings (27) formed in at least one of the friction surfaces and communicating with the outlet passage (24) of the pump means, said openings being configured to produce a hydrostatic  
layer together with the friction surfaces upon the  
25 delivery of pressure fluid.

2. A clutch arrangement according to Claim 1, characterized in that the pump means (10) is mounted on one  
clutch element (3, 4); and in that the openings (27)  
30 connected with the outlet passage (24) of said one clutch element are formed on the friction-surface of the same clutch element (3, 4).


3. A clutch arrangement according to Claim 1 or Claim 2, characterized in that the pump means includes a plurality of piston-pump housings (11) which extend radially and in uniform spaced relationship around the one clutch element (3, 4); and in that the pumps include piston rods (12) whose free ends are configured for axial activation by an excentric (17) mounted on the other clutch element (5, 6), when one clutch element rotates relative to the other clutch element.

4. A clutch arrangement according to any one of Claims 1-3, characterized in that at least one friction-surface is provided with grooves (29) which form drainage passages connected to the suction side (18) of the pump means, such as to form a closed pressure-fluid circuit.


5. A clutch arrangement according to any one of Claims 1-4, in which a plurality of separate pump-units are arranged on the pressure side of the pump means, characterized in that each pump unit (10) is assigned a given group of openings (27, 27') which communicate solely with the pressure-fluid outlet-passage (24, 24') of an associated pump-unit.

*Fig. 1*

1/1




*Fig. 2*



# INTERNATIONAL SEARCH REPORT

International Application No PCT/SE89/00371

<b>I. CLASSIFICATION OF SUBJECT MATTER</b> (If several classification symbols apply, indicate all) * According to International Patent Classification (IPC) or to both National Classification and IPC 4 <div style="text-align: center; font-family: monospace; font-size: 1.2em;">F 16 D 7/00</div>								
<b>II. FIELDS SEARCHED</b> <div style="text-align: center; font-size: 0.8em;">Minimum Documentation Searched 7</div> <table style="width: 100%; border-collapse: collapse;"> <tr> <th style="width: 30%; border-bottom: 1px solid black; font-size: 0.8em;">Classification System</th> <th style="border-bottom: 1px solid black; font-size: 0.8em;">Classification Symbols</th> </tr> <tr> <td style="padding: 5px;">IPC 4</td> <td style="padding: 5px;">F 16 D 7/00, 02; 9/00; 13/16; 25/12, 14</td> </tr> <tr> <td style="padding: 5px;">US C1</td> <td style="padding: 5px;">192: 56</td> </tr> </table>			Classification System	Classification Symbols	IPC 4	F 16 D 7/00, 02; 9/00; 13/16; 25/12, 14	US C1	192: 56
Classification System	Classification Symbols							
IPC 4	F 16 D 7/00, 02; 9/00; 13/16; 25/12, 14							
US C1	192: 56							
Documentation Searched other than Minimum Documentation to the Extent that such Documents are Included in the Fields Searched *								
<div style="text-align: center; font-family: monospace; font-size: 1.1em;">SE, NO, DK, FI classes as above</div>								
<b>III. DOCUMENTS CONSIDERED TO BE RELEVANT *</b>								
Category *	Citation of Document, 11 with indication, where appropriate, of the relevant passages 12	Relevant to Claim No. 13						
A	DE, A, 2 225 745 (J BOBST & FILS S.A.) 18 January 1973	1						
A	DE, A1, 2 536 310 (N.V. KEMPENSE STEEN- KOLENMIJNEN) 9 September 1976	1						
A	DE, A1, 3 638 596 (J.M. VOITH GMBH) 26 May 1988	1						
A	US, A, 3 107 765 (E.R. DAVIES) 22 October 1963	1						
<div style="display: flex; justify-content: space-between; font-size: 0.8em;"> <div style="width: 48%;"> <p>* Special categories of cited documents: 1*</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> </div> <div style="width: 48%;"> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>"A" document member of the same patent family</p> </div> </div>								
<b>IV. CERTIFICATION</b>								
Date of the Actual Completion of the International Search <div style="text-align: center; font-family: monospace; font-size: 1.1em;">1989-08-31</div>		Date of Mailing of this International Search Report <div style="text-align: center; font-family: monospace; font-size: 1.1em;">1989-09-07</div>						
International Searching Authority <div style="text-align: center; font-family: monospace; font-size: 1.1em;">Swedish Patent Office</div>		Signature of Authorized Officer <div style="text-align: center;">             Herman Phalen         </div>						

**THIS PAGE BLANK (USPTO)**